

# PRO-TECT II

FIBREWOVEN WALL COVERING  
EU & UK STANDARDS

- Perfect for cinemas
- Masks scratches, scrapes and bumps
- Protects high traffic areas
- Impact resistant and self-healing
- Low maintenance
- Does not fray or ravel
- Pill and fuzz resistant
- Colourfast and stain resistant
- Velcro compatible and tackable
- Soft and hardwearing
- Disguises soiling
- 100% recyclable
- Ideal for flat or curved surfaces
- Available in 3 standard colours



PRO-TECT II  
Wall Protection



**TECHNICAL SPECIFICATIONS**

Style: Ribbed Loop Construction

Thickness: 3 mm

Backing: Paper (Beige)

Weight: 920 g/sq. m

Roll width:

2 m x 25 Lin. m

**PERFORMANCE TESTS**

EU Flammability EN 13501

Euroclass Rating: B

Smoke: s2

Droplets: d0

ASTME E-84 : B, s2, d0

CE Certified

**FEATURES**

PRO-TECT II is a hardwearing wall finish specifically engineered for high traffic areas. Soft, flexible and attractive. Perfect for cinemas. Protect wall surfaces with this durable finish.

**COLOURS**

PRO-TECT II is available in a wide range of standard colours.

Custom colours are available upon request and review. Minimum order quantities may apply.

**INSTALLATION**

1. Direct glue to plasterboard, concrete or masonry.
2. Wall must be sound, clean and free from dust and dirt.

Recommended adhesives:

Laybond 81 (Plasterboard)

Laybond 48 (Concrete or masonry)

**DESIGN**

eomac's in-house Technical Team can provide design and layout support. Contact **eomac** for inquiries.

**MAINTENANCE**

Vacuum-clean.

Can be cleaned with carpet detergent. Do not use solvents containing acetone or hydrogen peroxide.





PRO-TECT  
Wall Protection

PRO-TECT II  
Wall Protection

For more information on PRO-TECT II, please contact us.  
[www.eomac.com](http://www.eomac.com) | [eomac@eomac.com](mailto:eomac@eomac.com)